

CLEANING SYSTEMS

CLEANING



MAIN FEATURES

- Process consisting of cleaning, rinsing and drying
- Plate dragged into the unit by the rolls
- Speed of the rolls, cleaning brushes speed and cleaning agent temperature managed by the computer
- Alternative and floating movement of the two cleaning brushes
- Automatic charging / discharging of the cleaning agent, Cleaning 45 model excluded
- Water supply necessary (Excluded Cleaning 45 or models equipped with the water filtration unit)



Optional

- Water filtration unit - excludes the necessity of water supply
- Pneumatic hydraulic system
- Customized in-let and out-let tables
- Customized feeding and exit belts
- Sticky plate





TECHNICAL DATA

45	66	86	96	120	140	180	MODEL
450 mm 17"	650 mm 25"	820 mm 32"	920 mm 36"	1150 mm 45"	1380 mm 54"	1780 mm 70"	Max. Plate Dimensions
140 mm 5"	220 mm 8"						Min. Length Plate
104x120 h 115	114x175 h 115	133x175 h 115	143x175 h 115	168x175 h 115	192x289 h 115	233x289 h 115	Dimension WxDxH
150	190	200	240	270	540	640	Weight kg
230V 50/60Hz 1PH+N+GND					230V/400V 50/60Hz 3PH-GND		Power Supply
2,5	2,5	2,5	3,5	3,5	5	8	Power kW
17	35				85		Solvet Tank Capacity (l)
17	39 OPTIONAL						Water Tank Capacity (l)

